Magnetic filtres & basket strainer

30 YEARS ELTERM®

Utility model Ru 069495

Polish manufacturer

- Effective filtering mesh of more than 600 meshes per cm²
- Effective ventilation
- Effective removal of mechanical contaminants
- Effective removal of ferrous contamination
- Easy and quick cleaning of the filter mesh and magnetic stack

Dryl 275 OC
Dryl 365 OC

	DRYL 37 OC 25/65	DRYL 60 OC 32/80	DRYL 95 OC 40/100	DRYL 144 OC 50/125	DRYL 275 OC 65/150	DRYL 365 OC* 80/200
Code	**712037**	**712060**	**712095**	**712144**	**712275**	**712365**
Insulation	Yes	Yes	Yes	Yes	Yes	Yes
	305 mm	405 mm	405 mm	500 mm	500 mm	800 mm
	175 mm	215 mm	215 mm	265 mm	420 mm	600 mm
	155 mm	190 mm	190 mm	220 mm	310 mm	500 mm
	3 kg	4 kg	6 kg	8,5 kg	23 kg	45 kg

*Half pallet dimensions + Dryl 365

	DRYL 37 25/65	DRYL 60 32/80	DRYL 95 40/100	DRYL 144 50/125		
Code	**702037**	**702060**	**702095**	**702144**		
Insulation	No	No	No	No		
	305 mm	405 mm	405 mm	500 mm		
	175 mm	215 mm	215 mm	265 mm		
	155 mm	190 mm	190 mm	220 mm		
	3 kg	4 kg	6 kg	8,5 kg		
Power max P at ΔT = 15K	to 37 kW	to 60 kW	to 95 kW	to 144 kW	to 275 kW	to 365 kW
Connection DN	25-1 " Int.	32-1¼" Int.	40-1½" Int.	50-2" Int.	Flange 2½" (DN65 PN16)	Flange 3" (DN80 PN16)
Flow Qmax	2,1 m3/h	3,5 m3/h	5,4 m3/h	8,3 m3/h	16,0 m3/h	21,2 m3/h
Temp. max.	110°C	110°C	110°C	110°C	110°C	110°C
Weight	2,4 kg	3,3 kg	4,8 kg	7,4 kg	19,5 kg	30,0 kg
Capacity V	0,7 l	1,3 l	2,4 l	4,0 l	7,1 l	15,7 l
Nominal pressure	6 bar	6 bar	6 bar	6 bar	6 bar	6 bar
Dz mm	76,1 x	88,9 x 3,2	114 x	133 x 4	159 x 4	219,1 x 4
A mm	158	180	205	235	340	400
H1mm	204	248	298	325	400	500
H2mm	260	305	365	385	470	570