

Technical parameters							
Model(s):	MHA-V16W/D2RN8-B2 / HBT-A160/240CDS90GN8-B2						
Air-to-water heat pump:	YES						
Water-to-water heat pump:	NO						
Brine-to-water heat pump:	NO						
Low-temperature heat pump:	NO						
Equipped with a supplementary heater:	YES						
Heat pump combination heater:	YES						
Declared climate condition:	AVERAGE						
Parameters are declared for medium-temperature application.							
Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	Prated	13.0	kW	Seasonal space heating energy efficiency	ηs	133.3	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = -7℃	Pdh	11.52	kW	Tj = -7℃	COPd	1.99	-
Tj = 2℃	Pdh	7.18	kW	Tj = 2℃	COPd	3.34	-
Tj = 7℃	Pdh	4.67	kW	Tj = 7℃	COPd	4.61	-
Tj = 12℃	Pdh	3.31	kW	Tj = 12℃	COPd	6.07	-
Tj = bivalent temperature	Pdh	11.52	kW	Tj = bivalent temperature	COPd	1.99	-
Tj = operating limit	Pdh	10.33	kW	Tj = operating limit	COPd	1.80	-
For air-to-water heat pumps: Tj = -15℃	Pdh	-	kW	For air-to-water heat pumps: Tj = -15℃	COPd	-	-
Bivalent temperature	Tbiv	-7	℃	For air-to-water heat pumps: Operation limit temperature	TOL	-10	℃
Cycling interval capacity for heating	Pcyh	-	kW	Cycling interval efficiency	COPcyc	-	-
Degradation co-efficient (**)	Cdh	0.9	--	Heating water operating limit temperature	WTOL	65	℃
Power consumption in modes other than active mode				Supplementary heater			
Off mode	Poff	0.014	kW	Rated heat output (**)	Psup	2.68	kW
Standby mode	Psb	0.014	kW	Type of energy input	Electrical		
Thermostat-off mode	Pto	0.024	kW				
Crankcase heater mode	Pck	0.000	kW				
Other items							
Capacity control	variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	4650	m³/h
Sound power level, indoors/outdoors	LWA	43 ^{a)} /68 44 ^{b)} /68	dB	For water-or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m³/h
Annual energy consumption	QHE	7895	kWh				
For heat pump combination heater:							
Declared load profile	XL			Water heating energy efficiency	ηwh	123	%
Daily electricity consumption	Qdec	6.35	kWh	Daily fuel consumption	Qfuel	-	kWh
Annual electricity consumption	AEC	1360	kWh	Annual fuel consumption	AFC	-	GJ
Contact details	GD Midea Heating & Ventilating Equipment Co. Ltd (Penglai industry road, Beijiao, Shunde, Foshan, Guangdong, P.R China)						
(*) For heat pump space heaters and heat pump combination heaters, the rated heat output Prated is equal to the design load for heating Pdesignh, and the rated heat output of a supplementary heater Psup is equal to the supplementary capacity for heating sup(Tj).							
(**) If Cdh is not determined by measurement then the default degradation coefficient is Cdh = 0,9.							
a) Represents : HB-A160/C***GN8-B2							
b) Represents : HBT-A160/240CD***GN8-B2							