



## Pellet Air

### TECHNICAL DATA

Thermic Power (at min-at max)	kW	2,6 - 5,5
Introduced thermal power (at max)	kW	6,2
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	$\eta_s$ [%]	83
Useful efficiency (at min-at max)	%	89 - 88
Heatable volume (at min-at max)	m <sup>3</sup>	73 - 154
CO <sub>2</sub> (min-max)	%	6,0 - 10,0
Emissions CO (13% O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	220 - 125
Emissions OGC (13%O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	3,0 - 2,0
Emissions NOX (13% O <sub>2</sub> ) (at min-at max)	mg/Nm <sup>3</sup>	120 - 99
Dust content at 13% O <sub>2</sub> (at min-at max)	mg/Nm <sup>3</sup>	20 - 10
Fuel Pellet	mm	Ø6 L=3÷40
Hopper capacity	kg	11
Hourly consumption (at min-at max)	kg/h	0,6 - 1,3
Autonomy (at min-at max)	h	18 - 8
Supply and frequency	V-Hz	230-50
Ignition electrical absorption	W	350
Operating electrical absorption (at max)	W	74
Chimney flue depression (at min-at max)	Pa	2 - 12
Mass of smoke (at min-at max)	g/sec	0,0 - 0,0
Exhaust fumes temperature (at min-at max)	°C	128 - 201
Distance from material comb. (back/side/under)	mm	300 / 200 / 0
Distance to material comb. (front/top)	mm	600 / 750
Exhaust fumes outlet (A)	Ø mm	80
Combustion air inlet (B)	Ø mm	60
Appliance Type (tightness)	Type	CC50

### PLUS

- 5 stars D.M. 186
- Back exhaust
- Remote control (optional)
- Cast iron burning pot
- Connection to the external thermostat
- Weekly programming
- Integrated Wi-Fi and Bluetooth

### AVAILABLE FINISHES

7025097		Steel White	EAN 8053859022077
7025098		Steel Red Bordeaux	EAN 8053859022084
7025099		Steel Anthracite	EAN 8053859022091

### CERTIFICATIONS

European standards  
Art. 15A B-VG 2015  
BImSchV 2015  
Regensburg  
München  
Stuttgart  
Aachen



EN 16510-1:2022 / EN 16510-2-6:2022  
CE



### STOVE PACKAGE

	L (cm)	H (cm)	P (cm)
	80	117	60
	Volume (m <sup>3</sup> )	0,56	
	Gross weight (kg)	63	
	Net weight (kg)	53	

### STORAGE

	N° (max)
	2
MAX 2	
1	

### TRANSPORT

66 pz